



SolidFeel® Rubber Underlay

Material Data Sheet

Product Description

Rubber Underlayment provides superb sound and moisture protection. This underlayment will absorb minor imperfections in the sub-floor, giving your laminate floor a smooth, even surface to float upon.

Technical Specification

Product Name	Rubber Underlayment
Code No.	Rubber 2.0; Rubber 3.0
Type	Sound + Vapor Barrier
Thickness	2.0mm; 3.0mm
Material	Rubber + Aluminum Foil + Non-woven Fabric
Regular Color	Green & Orange
Subfloor Compatibility	All Types
Floor Compatibility	Laminate
Installation Method	Floating
Recommended Usage	Residential & Light Commercial
Density	920kgs/m ³
IIC (Impact Insulation Class)	75db
STC (Sound Transmission Class)	74db
Sound Insulation	22db
Water Absorption 28 Days	★★★★★
Water Vapor Diffusion	★★★★★
Thermal Insulation	★★ 0.055m ² k/2
Moisture Proof	★★★★★
Suitable for Under-floor Heating	★★★★★
Durability	★★★★★
Mechanical Stress Rating	★★★★★
Package	Packed in rolls with PE wrapped

Product Features

1. Professionally protect floor from mildew, moisture and noise.
2. Offer people a quiet, healthy and comfortable environment with the high density and superior rubber material.
3. Suitable for under-floor heating.