
RHINO[®] Strive for perfection

The system floor pedestal type M3 from galvanized steel in combination with gaskets and optionally stringers type RO, RL and RM is used as substructure with raised access floor systems. The system floor pedestals are entirely made by Rhino, from the design to the production including galvanization.

The system floor pedestal type M3 creates the cavity for taking up installations. The system floor pedestal type M3 offers exceptional flexibility by its high loadability and the high adjustment range. The pedestals are infinitely adjustable on height and can therefore take up irregularities of the subfloor.

- Unique flexibility
- High loadability
- Easy installation
- High corrosion protection
- Zinc-whisker free
- Can be combined with stringer type RO, RL and RM flexibility



TECHNICAL DETAILS

| Upper pedestal part | |
|------------------------|---------------|
| Head plate | 80 x 80 mm |
| Thickness | 3.0 mm |
| Threaded bolt | M16 |
| Lower pedestal part | |
| Foot plate | 90 x 90 mm |
| Thickness | 3.0 mm |
| Tube (FFH 80 - 600 mm) | Ø 20 x 2.0 mm |

STATIC

| Ultimate load centric | ≥ 27 kN |
|-----------------------|---------|
| | |

CORROSION PROTECTION

| Corrosion protection class | Galvanized & blue passivated |
|----------------------------|------------------------------|
| Salt spray fog test | 72 hours |

PEDESTAL VARIANTS

| FFH | Part number | Adjustment range |
|---------------------------|-------------|------------------|
| 80 mm (HILTI customized) | M3-M16-80 | 70 - 110 mm |
| 90 mm (HILTI customized) | M3-M16-90 | 80 - 120 mm |
| 100 mm (HILTI customized) | M3-M16-100 | 90 - 130 mm |
| 150 mm | M3-M16-150 | 125 - 175 mm |
| 200 mm | M3-M16-200 | 175 - 225 mm |
| 250 mm | M3-M16-250 | 225 - 275 mm |
| 300 mm | M3-M16-300 | 275 - 325 mm |
| 350 mm | M3-M16-350 | 325 - 375 mm |
| 400 mm | M3-M16-400 | 375 - 425 mm |
| 450 mm | M3-M16-450 | 425 - 475 mm |
| 500 mm | M3-M16-500 | 475 - 525 mm |
| 550 mm | M3-M16-550 | 525 - 575 mm |
| 600 mm | M3-M16-600 | 575 - 625 mm |

FFH (Finished Floor Height) = floor tile + pedestal

Headquarters

1|1Rhino Technologies Co., Ltd.

Factory 2 Jishan Road, Jiangyin Wuxi 214445 China Phone +86 519 8988 3171

+86 519 8988 3901

Info@RhinoAccessFloors.com

www.RhinoAccessFloors.com

593, Tongjiang Road | Jintian Plaza 828-830 Changzhou 213022 | Jiangsu, China Managing Director: Mr. Zhongchun Dai Mobile: +86 159 6141 2270 Commercial Reg. No. 91320411564348344J

VAT Reg. No. 91320411564348344J