
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability. ©2010-2025 Rhino Technologies Co., Ltd. M5-M20-v2025 The system floor pedestal type M5 from galvanized steel in combination with gaskets and optionally stringers type RO, RL and RM is used as substructure with raised access floor systems. The system floor pedestals are entirely made by Rhino, from the design to the production including galvanization.

The system floor pedestal type M5 creates the cavity for taking up installations. The system floor pedestal type M5 offers exceptional flexibility by its high loadability and the high adjustment range. The pedestals are infinitely adjustable on height and can therefore take up irregularities of the subfloor.

- Unique flexibility
- High loadability
- Easy installation
- High corrosion protection
- Zinc-whisker free
- Can be combined with stringer type RO, RL and RM flexibility



TECHNICAL DETAILS

| Upper pedestal part | |
|--------------------------|---------------|
| Head plate | 80 x 80 mm |
| Thickness | 3.0 mm |
| Threaded bolt | M20 |
| Lower pedestal part | |
| Foot plate | 90 x 90 mm |
| Thickness | 3.0 mm |
| Tube (FFH 600 - 1200 mm) | Ø 25 x 2.5 mm |

STATIC

| Ultimate load centric | ≥ 30 kN |
|-----------------------|---------|

CORROSION PROTECTION

| Corrosion protection class | Galvanized & blue passivated |
|----------------------------|------------------------------|
| Salt spray fog test | 72 hours |

PEDESTAL VARIANTS

| FFH | Part number | Adjustment range |
|---------|-------------|------------------|
| 600 mm | M5-M20-600 | 570 - 630 mm |
| 650 mm | M5-M20-650 | 620 - 680 mm |
| 700 mm | M5-M20-700 | 670 - 730 mm |
| 750 mm | M5-M20-750 | 720 - 780 mm |
| 800 mm | M5-M20-800 | 770 - 830 mm |
| 850 mm | M5-M20-850 | 820 - 880 mm |
| 900 mm | M5-M20-900 | 870 - 930 mm |
| 950 mm | M5-M20-950 | 910 - 990 mm |
| 1000 mm | M5-M20-1000 | 960 - 1040 mm |
| 1050 mm | M5-M20-1050 | 1010 - 1090 mm |
| 1100 mm | M5-M20-1100 | 1060 - 1140 mm |
| 1150 mm | M5-M20-1150 | 1110 - 1190 mm |
| 1200 mm | M5-M20-1200 | 1160 - 1240 mm |

FFH (Finished Floor Height) = floor tile + pedestal

1|1Rhino Technologies Co., Ltd.

Factory 2 Jishan Road, Jiangyin Wuxi 214445 China

www.RhinoAccessFloors.com

Phone +86 519 8988 3171 +86 519 8988 3901 Commercial Reg. No. 91320411564348344J Info@RhinoAccessFloors.com

Headquarters 593, Tongjiang Road | Jintian Plaza 828-830 Changzhou 213022 | Jiangsu, China Managing Director: Mr. Zhongchun Dai Mobile: +86 159 6141 2270

VAT Reg. No. 91320411564348344J

Bank of China, Changzhou New Area Branch Tianan Industrial Village | Changzhou Xinbei | Jiangsu | China IBAN: 475458232608, Swift BIC: BKCHCNBJ95E Agricultural Bank of China, Head Office, P.R. China 311 Tongjiang Middle Road | Changzhou | Jiangsu | China IBAN: 10615114040014207, Swift BIC: ABOCCNBJ